

UK DECLARATION OF PERFORMANCE
Regulation (EU) 305/2011 No. 0001 — CPR-2013/07/01



No.: 124

1. **Unique identification code of the product-type** RAIS Visio 1, RAIS Visio 2, RAIS Visio 3
Attika Visio 1, Attika Visio 2, Attika Visio 3
2. **Type** Inset appliance burning solid fuel without hot water supply
3. **Intended use** Domestic room heater
4. **Manufacturer** RAIS A/S Telephone +45 98 47 90 33
Industrivej 20, Vangen Telefax +45 98 47 92 91
DK-9900 Frederikshavn, Denmark Webmail kundeservice@rais.dk
Homepage www.rais.com
5. **Authorised representative** n/a
6. **System of assessment AVCP** System 3
The notified *Danish Technological Institute - Identification no. 1235 Teknologiparken,*
laboratory *Kongsvang Allé 29, DK-8000 Århus C*
7. **Notified body** performed the determination of the product type on the basis of type testing under system 3 and issued test report
a. 300-ELAB-2080-EN
8. **Declared performance** Harmonized technical specification: EN 13229:2001/A2:2004/AC:2007

Essential characteristics		Performance		
Fire safety		<ul style="list-style-type: none"> Insulated flue 50 mm Skamotec 225 non-combustible panel board Distances are measured externally on the built-in box		
Reaction to fire	A1	Visio 1	Visio 2	Visio 3
Distance to combustible materials	rear	0	0	0
Minimum distances [mm] <i>For other installation or wall settings see instruction manual</i>	sides	167,5	167,5	-
	ceiling	735,5	735,5	735,5
	Front	1400	1200	1200
	Floor	385	385	385
Risk of burning fuel falling out	Pass			
OGC (mg/Nm ³ rel. 13 Vol-% O ₂)	45			
CO-emission of combustion products	0,092 % / 1150 mg/Nm ³			
NO _x (mg/Nm ³ rel. 13 Vol-% O ₂)	81			
Dust mg/Nm ³ at (rel. 13 Vol-% O ₂)	5			
Surface temperature	Pass			
Electrical safety	NPD			
Cleanability	Pass			
Maximum operating pressure	- bar			
Flue gas temperature T at nominal heat output	243 °C			
Mechanical resistance (to carry a chimney/flue)	NPD			
Thermal output				
Nominal heat output	7 kW			
Room heating output	7 kW			
Water heating output	- kW			
Energy efficiency ¹⁾	80 %			
Seasonal Efficiency $\eta_{S,on}$	70 %			

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

John Engell Nielsen, R&D Manager

Place FREDERIKSHAVN, DENMARK

Date 08-04-2022



Signature