

UK DECLARATION OF PERFORMANCE

Regulation (EU) 305/2011 No. 0001 — CPR-2013/07/01

No.: 831

- | | | |
|--|---|---|
| 1. Unique identification code of the product-type | RAIS Q-TEE 57 RAIS Q-TEE 65 RAIS Q-TEE 85 | ATTIKA Q-TEE 57 ATTIKA Q-TEE 65 ATTIKA Q-TEE 85 |
| 2. Type | Room heater burning solid fuel without hot water supply | |
| 3. Intended use | Domestic room heater | |
| 4. Manufacturer | RAIS A/S Industrivej 20, Vangen DK-9900 Frederikshavn, Denmark | Telephone +45 98 47 90 33 Telefax +45 98 47 92 91 Webmail kundeservice@rais.dk Homepage www.rais.com |
| 5. Authorised representative | n/a | |
| 6. System of assessment AVCP | System 3 | |
| 7. Notified body | The notified laboratory <i>Danish Technological Institute - Identification no. 1235 Teknologiparken, Kongsvang Allé 29, DK-8000 Århus C</i> | |
- performed the determination of the product type on the basis of type testing under system 3 and issued test report
- a. 300-ELAB-1521-EN-rev1

- 8. Declared performance** Harmonized technical specification: EN 13240:2003/A2:2004

| Essential characteristics | | Performance | |
|---|-----------------------|------------------|----------------|
| Fire safety | | | |
| Reaction to fire | A1 | Uninsulated flue | Insulated flue |
| Distance to combustible materials | rear | 350 mm | 275 mm |
| Minimum distances [mm] | sides | 275 mm | 225 mm |
| <i>For other installation or wall settings see instruction manual</i> | ceiling | 800 mm | 800 mm |
| | Front | 650 mm | 650 mm |
| Risk of burning fuel falling out | Pass | | |
| OGC (mg/Nm ³ rel. 13 Vol-% O ₂) | 58 | | |
| CO-emission of combustion products | 0,0987 % | | |
| NO _x (mg/Nm ³ rel. 13 Vol-% O ₂) | 79 | | |
| Dust at (rel. 13 Vol-% O ₂) | 20 mg/Nm ³ | | |
| Surface temperature | Pass | | |
| Electrical safety | NPD | | |
| Cleanability | Pass | | |
| Maximum operating pressure | - bar | | |
| Flue gas temperature T at nominal heat output | 283° C | | |
| Mechanical resistance (to carry a chimney/flue) | NPD | | |
| Thermal output | | | |
| Nominal heat output | 4,1 kW | | |
| Room heating output | 4,1 kW | | |
| Water heating output | - kW | | |
| Energy efficiency η | 80 % | | |
| Seasonal Efficiency $\eta_{S,on}$ | 70 % | | |

- 9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by:

John Engell Nielsen, R&D / Quality Manager

Place FREDERIKSHAVN, DENMARK

Date 31-03-2022


 Signature